

### **Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

### **Listing of Claims:**

Claim 1 (currently amended): A method for removing a red eye from an image, comprising:

calculating a weighted red value for each pixel in the image, wherein the weight red value for a pixel is based on (1) red, green, and blue color values of the pixel and (2) a luminance of each the pixel in the image;

selecting a plurality of pixels in the image having weighted red values greater than a threshold as red eye pixels; and

correcting the red eye pixels to remove the red eye from the image.

Claim 2 (currently amended): The method of claim 1, wherein said calculating comprises:

$$f_1 = \frac{c_1^{(1)}r + c_2^{(1)}g + c_3^{(1)}b}{Y},$$

wherein  $f_1$  is the weighted red value,  $r$  is the red color value,  $g$  is the green color value,  $b$  is the blue color value,  $c_1^{(1)}$  is a first weight given to the red color value,  $c_2^{(1)}$  is a second ~~weigh~~ weight given to the green color value,  $c_3^{(1)}$  is a third weight given to the blue color value, and  $Y$  is the luminance.

Claim 3 (original): The method of claim 2, wherein  $c_1^{(1)}$  is 0.5,  $c_2^{(1)}$  is 0.5,  $c_3^{(1)}$  is -1,  $Y = 0.299r + 0.587g + 0.114b$ , and the threshold is 0.5.

Claim 4 (currently amended): The method of claim 2, prior to said correcting, further comprising:

calculating another weighted red value for each pixel in the image, wherein said another weight red value for a pixel is based on (1) ~~from~~ the red, the green, the blue color values of the pixel, and (2) the luminance of each the pixel in the image, said calculating another weighted red value comprising:

$$f_2 = \frac{c_1^{(2)}r + c_2^{(2)}g + c_3^{(2)}b}{Y},$$

wherein  $f_2$  is said another weighted red value,  $c_1^{(2)}$  is another first weight given to the red color value,  $c_2^{(2)}$  is another second weight given to the green color value, and  $c_3^{(2)}$  is another third weight given to the blue color value; and

selecting another plurality of pixels in the image having another weighted red values greater than another threshold as additional red eye pixels.

Claim 5 (previously presented): The method of claim 4, wherein  $c_1^{(2)}$  is 0.6667,  $c_2^{(2)}$  is 0.3333,  $c_3^{(2)}$  is -1.0,  $Y = 0.299r + 0.587g + 0.114b$ , and the threshold is 0.5.

Claim 6 (previously presented): The method of claim 1, prior to said correcting, further comprising:

grouping a plurality of red eye pixels that are contiguous into a red eye region;

determining if the red eye region comprises a substantially round pupil; and

rejecting the plurality of red eye pixels when the red eye region does not comprise a substantially round pupil.

Claim 7 (previously presented): The method of claim 6, wherein said determining if the red eye region comprises a substantially round pupil comprises:

determining a geometric center of the red eye region;

for each radius in a range of radii, determining a difference between (1) weighted red values of red eye pixels located at a radius and at a range of angles about the geometric center and (2) weighted red values of red eye pixels located at a next radius in the range of radii and at the range of angles;

selecting one radius in the range of radii that provides a largest difference as a pupil radius for the red eye region;

determining a first ratio of (1) a first number of red eye pixels located in a circle having the pupil radius to (2) an area of the circle;

determining a second ratio of (1) a second number of red eye pixels in a ring having an inner radius of the pupil radius and an outer radius of a maximum radius in the range of radii to (2) an area of the ring; and

determining a difference between the first ratio and the second ratio, wherein the red eye region does not comprise a substantially round pupil when the difference is less than a threshold.

Claim 8 (original): The method of claim 7, wherein the range of radii ranges from 0.5 to 1.5 times a distance from the geometric center to a farthest red eye pixel in the red eye region.

Claim 9 (previously presented): The method of claim 6, further comprising:

determining if the red eye region is too close to another red eye region formed by grouping another plurality of red eye pixels that are contiguous; and

rejecting the plurality of red eye pixels when the red eye region is too close to said another red eye region.

Claim 10 (previously presented): The method of claim 9, wherein said determining if the red eye region is too close to another red eye region comprises:

determining if a geometric center of the red eye region is within a range of distances of another geometric center of said another red eye region, wherein the range of distances is proportional to a pupil radius of the red eye region.

Claim 11 (previously presented): The method of claim 10, further comprising determining the pupil radius as follows:

determining the geometric center of the red eye region;

for each radius in a range of radii, determining a difference between (1) weighted red values of red eye pixels located at a radius and at a range of angles about the geometric center and (2) weighted red values of red eye pixels located at a next radius in the range of radii and at the range of angles; and

selecting one radius in the range of radii that provides a largest difference as a pupil radius for the red eye region.

Claim 12 (previously presented): The method of claim 11, wherein the range of distances comprises 10 to 14 times the pupil radius.

Claim 13 (previously presented): The method of claim 9, further comprising:

determining if the red eye region is proximate to a facial region; and

rejecting the plurality of red eye pixels when the red eye region is not proximate to a facial region.

Claim 14 (previously presented): The method of claim 13, wherein said determining if the red eye region is proximate to a facial region comprising:

generating a histogram for pixels in a ring having an inner and outer radii proportional to a pupil radius of the red eye region;

selecting a most common color value in the histogram;

comparing the most common color to a range of threshold skin colors; and

rejecting the plurality of red eye pixels when the most common color in the histogram is not within the range of the threshold skin colors.

Claim 15 (original): The method of claim 14, wherein said comparing comprises comparing the most common color value in HSV color space to the range of threshold skin colors in HSV color space.

Claim 16 (previously presented): The method of claim 14, further comprising determining the pupil radius as follows:

determining a geometric center of the red eye region;

for each radius in a range of radii, determining a difference between (1) weighted red values of red eye pixels located at a radius and at a range of angles about the geometric center and (2) weighted red values of red eye pixels located at a next radius in the range of radii and at the range of angles; and

selecting one radius in the range of radii that provides a largest difference as a pupil radius for the red eye region.

Claim 17 (previously presented): The method of claim 16, wherein the inner and the outer radii comprises of 4 to 9 times the pupil radius.

Claim 18 (previously presented): The method of claim 13, further comprising:

determining if the red eye region is proximate to a sclera; and

rejecting the plurality of red eye pixels when the red eye region is not proximate to a sclera.

Claim 19 (previously presented): The method of claim 18, wherein said determining if the red eye region is proximate to a sclera comprises:

generating a luminance histogram for pixels in a ring having an inner and outer radii proportional to a pupil radius of the red eye region;

selecting a brightest color in the luminance histogram;

determine a ratio between a number of pixels in the ring having the brightest color to a number of red eye pixels within a circle having the pupil radius; and

rejecting the plurality of red eye pixels when the ratio is less than a threshold.

Claim 20 (previously presented): The method of claim 19, further comprising determining the pupil radius as follows:

determining a geometric center of the red eye region;

for each radius in a range of radii, determining a difference between (1) weighted red values of red eye pixels located at a radius and at a range of angles about the geometric center and (2) weighted red values of red eye pixels located at a next radius in the range of radii and at the range of angles; and

selecting one radius in the range of radii that provides a largest difference as a pupil radius for the red eye region.

Claim 21 (previously presented): The method of claim 20, wherein the inner and the outer radii comprises 2 to 5 times the pupil radius.

Claim 22 (currently amended): The method of claim 1, wherein the method is implemented in software executed by a computer or firmware stored on a computer or firmware readable medium in ~~embedded into~~ digital cameras, printers, scanners, or mobile phones.

Claim 23 (original): A method for removing a red eye from an image, comprising:

calculating a weighted red value for each pixel in the image from a luminance, a red chrominance, and a blue chrominance values of each pixel in the image, comprising:

$$f_1 = \frac{1.41514(Cr - 128) + 1.23014(Cb - 128)}{Y},$$

wherein  $f_1$  is the weighted red value,  $Cr$  is the red chrominance value,  $Cb$  is the blue chrominance value, and  $Y$  is the luminance value;

selecting a plurality of pixels in the image having weighted red values greater than a threshold as red eye pixels; and

correcting the red eye pixels in the image.

Claim 24 (previously presented): The method of claim 23, prior to said correcting, further comprising:

calculating another weighted red value for each pixel in the image from the luminance, the red chrominance, and the blue chrominance values of each pixel in the image, comprising:

$$f_2 = \frac{0.69662(Cr - 128) - 1.88671(Cb - 128)}{Y},$$

wherein  $f_2$  is said another weighted red value; and

selecting another plurality of pixels in the image having another weighted red values greater than another threshold as additional red eye pixels.

Claim 25 (currently amended): The method of claim 23, wherein the method is implemented in software executed by a computer or firmware stored on a computer or firmware readable medium in ~~embedded into~~ digital cameras, printers, scanners, or mobile phones.